


SLIM

Apparecchio LED per installazione ad incasso in battuta in controsoffitto.
Cornice e corpo dissipante in lega di alluminio pressofusa verniciata bianca.
Schermo diffusore in policarbonato opale e molle in acciaio armonico per il fissaggio a controsoffitto di spessore fino a 15 mm. Alimentazione elettronica inclusa, da collocare a lato del prodotto.

LED fixture for false ceiling recessed installation.
Frame and dissipater made of die-casting aluminum alloy, white painted.
Diffuser made of opal polycarbonate and clips made of harmonic steel, for fixing to the false ceiling of thickness up to 15 mm. Electronic driver included, to be placed next to the fixture.



9W	13W	20W
H 100	H 100	H 100
Ø 110	Ø 145	Ø 210-215

SLIM TONDO CRI>90


CRI >90

SLIM ROUND CRI>90

IL PRODOTTO RISPONDEnte AI REQUISITI PER EDIFICI PUBBLICI D.M. 11 OTT 2017 (C.A.M. Edilizia)

THE PRODUCT COMPLIES WITH THE REQUIREMENTS FOR PUBLIC BUILDINGS, MINISTERIAL DECREE OF 11th OCT 2017

POWER	Ø (mm)	H (mm)	FLUX	3000K <input type="checkbox"/>	FLUX	4000K <input type="checkbox"/>
9W	125	25	950 lm	11820.01	970 lm	11819.01
13W	160	26	1210 lm	11818.01	1280 lm	11817.01
20W	230	28	1950 lm	11816.01	2000 lm	11815.01




9W	13W	20W
H 100	H 100	H 100
L 95	L 145	L 210-215
W 95	W 145	W 210-215

SLIM QUADRATO CRI>80

SLIM SQUARE CRI>80

POWER	L (mm)	H (mm)	FLUX	3000K <input type="checkbox"/>	FLUX	4000K <input type="checkbox"/>
9W	110	24	1080 lm	11812.01	1100 lm	11813.01
13W	160	26	1400 lm	11808.01	1475 lm	11807.01
20W	230	28	2250 lm	11806.01	2300 lm	11805.01



KIT DI EMERGENZA
da installare sul controsoffitto
a lato del prodotto.

EMERGENCY KIT
to place on the false ceiling
next to the fixture.

CODE	TIME	A (mm)	D (mm)	H (mm)	L (mm)
18002.99	1h	46	59	23	138

Flusso in emergenza
Emergency flux

SLIM 9W	70%
SLIM 13W	48%
SLIM 20W	30%